



Buckets Elevator

Volume per bucket: 1,3 L
 Bucket width: 380 mm
 Transport capacity : 6 m³/h
 Power supply: 220 V / 60 Hz; 0.75 kW
 Output height: 3400 mm
 Feeding height: 500 mm

Machine Features :
 The conveyor is made of 304stainless steel sanitary construction and food grade polypropylene (PP) bucket.
 Automatic stop & start sensor control with filling from hopper or to scale

All parts and buckets with safety and easy removal , machine with automatic chain tighten device and overload protection.

Custom design and size available

Bucket Volume	2L/ 4L
Overall height	3896mm
Discharge height	3256mm
Conveying speed	10m-12m/min
Bucket material	food grade plastic bucket
Voltage	3P 380V/ 220V,50Hz/60Hz 0.75KW



Modular Belt Type Elevator S-Shaped type

Machine Features :
 The conveyor is made of 304stainless steel sanitary construction and food grade polypropylene (PP)belt , with good appearance, not easily deformed, belt material resistant to high and low temperatures.

The machine can easily interface with various types of feeding devices.

Easy installation and disassembly, the belt can be directly washed.

Optional parts :
 Food grade plastic belt (flat or dimpled)
 Custom design and size available

Overall belt width	602mm
Available belt width	450mm
Side board height	102mm
Middle baffle height	94mm
Discharge height	3520mm
Infeed height	750mm
Conveying speed	20m-30m/min
Belt character	food grade plastic belt
Voltage	3P 380V/ 220V,50Hz/60Hz



Inclined Modular Belt Type Elevator

Machine Features :

The conveyor is made of 304 stainless steel sanitary construction and food grade polypropylene (PP) belt , with good appearance, not easily deformed, belt material resistant to high and low temperatures.

The machine can easily interface with various types of feeding devices.

Easy installation and disassembly, the belt can be directly washed.

Optional parts :

Food grade plastic belt (flat or dimpled)

Custom design and size available

Overall belt width	400mm
Available belt width	300mm
Side wall height	100mm
Middle baffle height	75mm
Discharge height	3198mm
Infeed height	490mm
Conveying speed	17m-25m/min
Belt	food grade plastic belt
Voltage	3P 380V/ 220V,50Hz/60Hz
Packaging Size and Gross weight : Fumigated wooden case	5700 (L) *810(W)*930mm(H)/ 460KG



Inclined PU Belt Conveyor

Machine Features :

The conveyor is made of 304 stainless steel sanitary construction and food grade polypropylene (PU) belt , with good appearance, not easily deformed, belt material resistant to high and low temperatures.

The machine can easily interface with various types of feeding devices.

Easy installation and disassembly, the belt can be directly washed.

Optional parts :

Food grade plastic belt (flat or dimpled)

Custom design and size available

Overall belt width	450mm
Useful Belt Width	230mm
Middle baffle height	70mm
Discharge height :	3550mm
Infeed height	435mm
Conveying capacity	20m-25m/min
Belt	food grade PU belt
Voltage	3P 380V/ 220V,50Hz/60Hz
Packaging Size and Gross Weight : fumigated wooden case	7350 (L) *1000(W)*1400mm(H)/ 820KG

Inclined Screw type Conveyor



Product features

- 1) Worked with packaging machine for feeding variety powdery products.
- 2) Two motors used for screw feeding and hopper vibrating, separately control.
- 3) According to the material character to adjust the hopper amplitude.
- 4) The design of the separation between the hopper and auger screw makes the installation and disassembling easier.
- 5) Unique dust-proof design, keep the products clean and hygiene
- 6) The auger screw has the forward and reverse function, which is easy to clean materials inside the auger screw

Model	MF-S2-2K	MF-S2-3K	MF-S2-5K	MF-S2-7K	MF-S2-8K	MF-S2-12K
Charging Capacity	2m³/h	3m³/h	5 m³/h	7 m³/h	8 m³/h	12 m³/h
Diameter of pipe	Φ102	Φ114	Φ141	Φ159	Φ168	Φ219
Total power	0.58KW	0.78W	1.53KW	1.53KW	3.03KW	4.03KW
Total weight	100kg	130kg	170kg	200kg	220kg	270kg
Hopper volume	100L	200L	200L	200L	200L	200L